



Certificate of Analysis

Vessel / Object: MAERSK MARU (9581447)
Location: Port Arthur, TX / GT Gulfway (United States)
Job Type: Load
Product Grade: CUR 95 Ron Gasoline
Client Reference: Atlantic Trading & Marketing Inc. / HV50995

Job No: 160-24-02672
Date Sampled: 06/05/24
Date Tested: 06/06/24
Version: 1 / 06 Jun 2024 13:08

<u>Sample</u>	<u>Sample ID, Type & Description</u>					
160-24-02672-192	4P Running After Load					
<u>Method</u>	<u>Test</u>	<u>Min</u>	<u>Max</u>	<u>Result</u>	<u>Units</u>	<u>Remarks</u>
ASTM D5191	DVPE @ 100F° (ASTM EQ)			8.64	psi	
ASTM D5705##	Hydrogen Sulfide Content in Vapor			0	ppm v/v	

<u>Sample</u>	<u>Sample ID, Type & Description</u>					
160-24-02672-196	4S Running After Load					
<u>Method</u>	<u>Test</u>	<u>Min</u>	<u>Max</u>	<u>Result</u>	<u>Units</u>	<u>Remarks</u>
ASTM D5191	DVPE @ 100F° (ASTM EQ)			8.59	psi	
ASTM D5705##	Hydrogen Sulfide Content in Vapor			0	ppm v/v	

<u>Sample</u>	<u>Sample ID, Type & Description</u>					
160-24-02672-200	8P Running After Load					
<u>Method</u>	<u>Test</u>	<u>Min</u>	<u>Max</u>	<u>Result</u>	<u>Units</u>	<u>Remarks</u>
ASTM D5191	DVPE @ 100F° (ASTM EQ)			8.54	psi	
ASTM D5705##	Hydrogen Sulfide Content in Vapor			0	ppm v/v	

<u>Sample</u>	<u>Sample ID, Type & Description</u>					
160-24-02672-204	8S Running After Load					
<u>Method</u>	<u>Test</u>	<u>Min</u>	<u>Max</u>	<u>Result</u>	<u>Units</u>	<u>Remarks</u>
ASTM D5191	DVPE @ 100F° (ASTM EQ)			8.50	psi	
ASTM D5705##	Hydrogen Sulfide Content in Vapor			0	ppm v/v	

<u>Sample</u>	<u>Sample ID, Type & Description</u>					
160-24-02672-229	4P,4S,8P,8S Volumetric Composite After Load					
<u>Method</u>	<u>Test</u>	<u>Min</u>	<u>Max</u>	<u>Result</u>	<u>Units</u>	<u>Remarks</u>
ASTM D4052	Gravity by Digital Density Meter					
	API Gravity @60°F			57.4	°	
	Density @15°C	720.0	775.0	749.1	kg/m ³	
Visual	Visual Appearance at 20°C	Clear & Bright		Clear and Bright		
ASTM D130	Copper Strip Corrosion Rating @50°C/122°F for 3 Hours		1	1A		
ASTM D86	Distillation Evaporated					
	IBP	30		31.6	°C	
	10%	40	70	50.9	°C	
	50%	80	115	89.6	°C	
	90%		180	159.6	°C	

AmSpec LLC - 4665 Jerry Ware Dr. - Beaumont - TX - 77705 - EPA ID# 1285

This document is issued by the Company subject to the Terms and Conditions at <https://www.amspecgroup.com/terms-conditions>. Any holder of this document is advised that information contained herein reflects the Company's findings at the time and place of its intervention only and within the scope of the Client's instructions. The Company's sole responsibility is to its Client and the Company disclaims any liability to third parties. Any alteration, forgery or falsification of the content or appearance of this document is unlawful.



Certificate of Analysis

Vessel / Object: MAERSK MARU (9581447)
Location: Port Arthur, TX / GT Gulfway (United States)
Job Type: Load
Product Grade: CUR 95 Ron Gasoline
Client Reference: Atlantic Trading & Marketing Inc. / HV50995

Job No: 160-24-02672
Date Sampled: 06/05/24
Date Tested: 06/06/24
Version: 1 / 06 Jun 2024 13:08

Sample 160-24-02672-229 **Sample ID, Type & Description** 4P,4S,8P,8S Volumetric Composite After Load

<u>Method</u>	<u>Test</u>	<u>Min</u>	<u>Max</u>	<u>Result</u>	<u>Units</u>	<u>Remarks</u>
ASTM D86	Distillation Evaporated					
	FBP		215	202.6	°C	
	Residue		2.0	0.9	%vol	
	% Evaporated @70°C			32.9	%vol	
ASTM D381	Existent Gum Content		4.0	< 0.5	mg/100ml	
ASTM D2699	Research Octane Number	95.0		95.2		
ASTM D2700	Motor Octane Number	85.0		85.6		
ASTM D4814	Antiknock Index (R+M)/2			90.4		
ASTM D3606-20e1	Benzene		1.00	0.41	%vol	
ASTM D1319	Hydrocarbon types by FIA (Aromatics, Olefins & Saturates)					
	Aromatics		35	30.8	%vol	
	Olefins		18.0	10.0	%vol	
	Aromatics and Olefins		45.0	40.8	%vol	
ASTM D6304A	Water Concentration			297	ppmw	
ASTM D525	Oxidation Stability @100°C	360		> 360	mins	
ASTM D4815	Oxygenates in Gasoline					
	Total Oxygen Content		2.70	2.57	%wt	
	Oxygenates			14.24	%wt	
	Methanol		3.0	< 0.20	%vol	
ASTM D5191	DVPE @ 100F° (ASTM CALC AVG)		8.7	8.57	psi	
ASTM D2622-16	Total Sulfur Content (Origin)		30	10.8	mg/kg	
ASTM D4952	Doctor Test	Negative		Negative		
ASTM D3227	Mercaptan Sulfur		0.0015	0.0005	%wt	
ASTM D3231	Phosphorus		1	< 0.20	mg/L	
ASTM D3831	Manganese Content of Gasoline		0	< 0.20	mg/L Mn	
ASTM D3237	Lead		5	< 2.5	mg/L	
ASTM D5708A**	Silicon Content			< 1.0	mg/kg	
ASTM D7536	Total Chloride Concentration			< 0.2	mg/kg	